

REVOLUTIONARY  
PANIC EXIT  
HARDWARE FOR  
SECURITY AND  
DURABILITY.

ARM-A-DOR® MAXIMUM-  
SECURITY PANIC HARDWARE.



Get aggressive in the fight against back door break-ins. Arm-A-Dor panic hardware gives you protection against forced entry comparable to a drop-bar while still providing a quick way out for employees and customers.

Rugged Arm-A-Dor panic hardware is made with 12-gauge telescopic steel tubing to withstand attacks and the abuse of countless openings and closings. And it meets the UL 305 and 10B standards for panic and fire exit hardware and the NFPA 101 Life Safety Code enforced by fire marshals and building inspectors.

Keep your people and your business safe. Call now for more information.

**1-800-826-7652**



From Sargent & Greenleaf, Inc.

[www.arm-a-dor.com](http://www.arm-a-dor.com)





## Take control with an investment in Arm-A-Dor® security.

### Three Products in One

- Locking Bar Security
- Panic Exit Device with UL listing U.S. and Canada
- Loss Prevention Alarm (when alarm equipped)

### Drop Bar Security

- Provides resistance to forced entry attacks per UL1034 standard
- Locking members extend 1-1/2" over frame on each side

### Code Conformance

- UL 305 Panic Device Rating
- UL 10B, Fire Exit Hardware, 3 hrs. at 2000° F
- Dade County (Florida) Product Control Approved No. 96-1127.02 (Hurricane)
- NFPA 101 Life Safety Code
- UBC/BOCA
- ANSI 156.3
- City of New York, Dept. of Buildings, MEA 292-96-E

### Works with ANY Security System

- Alarm operated by standard or interchangeable core mortise cylinder
- Optional remote switch operates timed delay egress systems, cameras or other alarms

### Alarmed Models

- Battery operated – approx 1-yr. life; two 9-Volt batteries included
- Low battery audible warning signal
- Loud alarm, 1 horn; 95 db @ 10 ft.
- Tamper Alarm
- Nuisance Alarm
- Re-arm reminder feature
- Optional AC adapter or hardwire kits
- Optional delay arming feature

### Flexible Installation

- Quick Install models with pre-assembled 36" and 48" units
- Easy to follow six-step installation instructions
- Retrofit or new construction work
- Non-handed
- Fits doors 36" to 48" wide
- Double-door applications work on fixed or removable center mullions or without mullion
- No special door preparation
- Works on any door or frame
- Shipped with required hardware for standard single door applications

### Relocking Choices

- Automatic or manual models

### Mechanical Efficiency and Durability

- Roller design deadbolt means reduced friction and wear
- Touch-bar operates with straight push-through motion
- Weather and water resistant

Product Number	Description	Alarm*	Fits Door Widths	Fits Jamb's Up To	Finish
----------------	-------------	--------	------------------	-------------------	--------

### Complete Product Assemblies

A101-001	Automatic Re-Lock	No	3' to 4'	6-3/4"	US28
A101-002	Automatic Re-Lock	Yes	3' to 4'	6-3/4"	US28
A101-F01	Automatic-Fire Rated	No	3' to 4'	6-3/4"	US28
A101-F02	Automatic-Fire Rated	Yes	3' to 4'	6-3/4"	US28
A101-012	36" Automatic Re-Lock	No	3' ONLY	5-3/4" ONLY	US28
A101-013	36" Automatic Re-Lock	Yes	3' ONLY	5-3/4" ONLY	US28
A101-014	48" Automatic Re-Lock	No	4' ONLY	5-3/4" ONLY	US28
A101-015	48" Automatic Re-Lock	Yes	4' ONLY	5-3/4" ONLY	US28
A102-001	Manual Re-Lock	No	3' to 4'	6-3/4"	US28
A102-002	Manual Re-Lock	Yes	3' to 4'	6-3/4"	US28

### Optional Kits

A103-003	Alarm Sub-Assembly
A103-002	RX Switch (For wiring to existing systems—one individual kit)
A104-001	Low Profile Installation Kit (For door jamb's greater than 6-3/4" up to 12-3/4")
A106-001	Standard Double Door Kit (For door jamb's up to 6-3/4")
A106-002	Low Profile Double Door Kit (For door jamb's greater than 6-3/4")
A107-001	A/C Adapter Kit (For plug in with battery back-up)
A107-002	A/C Adapter Hardwire Kit (For wiring to electrical system w/battery backup)

### Deadbolts

1881-003	Sliding Deadbolt with Padlock Locking Hasp & Strike
1883-003	Sliding Deadbolt Keylocking with Strike

\* Alarm Models A101-002, A101-013, A101-015, A102-002 and A101-F02 require two 9-volt batteries (included) and a standard 1-1/8" mortise cylinder with straight cam (not included).



www.sargentandgreenleaf.com  
www.stanleysecuritysolutions.com